



## Type FL INCH

SHAFT DIA	SHAFT TOLERANCE	
	DU	DX
12 TO 75	f7	h8
> 75	h8	h8

Part No	E	C	B bolt	L	T	W	A	F
0.5 FL1-08E-DU FL1-08E-DX	0.625	2.25	0.312	3	0.312	0.937	2.125	0.25
0.625 FL1-10E-DU FL1-10E-DX	0.625							
0.75 FL1-12E-DU FL1-12E-DX	0.75					1		
0.875 FL2-14E-DU FL2-14E-DX	0.875	2.5	0.375	3.5	0.375	1.125	2.5	0.375
1 FL2-16E-DU FL2-16E-DX	1					1.187		
1.125 FL3-18E-DU FL3-18E-DX	1	3.125	0.5	4.312	0.437	1.312	3.125	0.5
1.25 FL3-20E-DU FL3-20E-DX	1.25					1		
1.375 FL4-22E-DU FL4-22E-DX	1.375	3.625	0.5	4.75	0.562	1.437	3.75	0.625
1.5 FL4-24E-DU FL4-24E-DX	1.5					1.75		
1.625 FL4-26E-DU FL4-26E-DX	1.5					1.75		
1.75 FL5-28E-DU FL5-28E-DX	1.75	4	0.5	5.25	0.625	2	4.25	0.625
1.875 FL6-30E-DU FL6-30E-DX	1.875	4.375	0.5	5.625	0.625	2.25	4.625	0.812
2 FL6-32E-DU FL6-32E-DX	2					2.312		
2.25 FL7-36E-DU FL7-36E-DX	2.25	5.125	0.625	6.5	0.687	2.5	5.375	0.875
2.5 FL8-40E-DU FL8-40E-DX	2.5	5.625	0.625	6.875	0.75	2.75	5.625	1
2.75 FL8-44E-DU FL8-44E-DX	2.5							
3 FL9-48E-DU FL9-48E-DX	3	6	0.75	7.75	0.875	3.125	6.75	1.125
3.5 FL10-56E-DU FL10-56E-DX	3	7.75	0.75	9.5	1	3.5	8.25	1.25
4 FL10-64E-DU FL10-64E-DX	3							